



Acendo Vibe[™] **Conferencing Sound Bar**

ACV-2100GR, Grey (FG4121-00GR) ACV-2100BL, Black (FG4121-00BL) ACV-2100BU, Blue (FG4121-00BU)



Overview

Acendo Vibe 2100 is an expertly designed conferencing sound bar for meeting spaces. Featuring Sound by JBL, the connectivity that a professional environment requires, and a look that holds up to modern workspace architecture, Acendo Vibe supports the high standards of today's workforce.

Acendo Vibe utilizes HARMAN's audio expertise with integrated JBL speakers, farfield microphones, and DSP algorithms to ensure everyone in the room hears and is heard clearly. Bluetooth connectivity allows for wireless sharing of content. Additionally, dedicated audio inputs and outputs allow Acendo Vibe to easily integrate with other room technology, such as hearing-enhancement systems.

Common Applications

The Acendo Vibe 2100 conferencing sound bar is ideal for corporate meeting spaces that require audio-only conferencing or that utilize an external USB camera. For a more complete solution, HARMAN's Acendo Vibe 5100 has an integrated camera, HDMI connectivity, and CEC display control.

Features

- Sound by JBL Hear everything said in the meeting with speakers, microphones, and DSP algorithms from JBL.
- Elegant Design Modern office environments are designed to attract and retain the most talented
 employees through the use of elegant interior design and the use of tactile materials, such as fabrics. Acendo
 Vibe is built using high-quality materials and is available in three colors designed to complement any interior
 design.
- USB and Bluetooth Connectivity Use Acendo Vibe in BYOD applications with a user's laptop or mobile
 phone, or use it with Acendo Core to create a complete, highly optimized meeting solution.
- Integrated Mounting Bracket The integrated wall mount facilitates installation by a single person. This
 mount allows customers to connect and route all the cabling with Acendo Vibe on the wall and then simply
 rotate Acendo Vibe into position.

Specifications

cifications	1
GENERAL	
Dimensions	3" x 23 1/2" x 4 1/8" (76 mm x 590 mm x 105 mm)
	Depth without wall mount spacers: 3 15/16" (100 mm
Weight	TBA
Mounting Options	Built-in wall mount with hinge that allows installers to
	connect and manage cables when AMX Acendo Vibe i
	hanging on the wall.
	Installed rubber feet that allow AMX Acendo Vibe to
	sit on a credenza or tabletop. Rubber feet can be
	removed for installation on a wall; however, it is
	important to note that rubber feet must be present
	when resting on a table or the sound will be severely
	degraded.
CONNECTORS	
Analog Stereo Input	1/8" mini-Stereo Jack
Analog Stereo Output	1/8" mini-Stereo Jack
Optical Stereo Input	TOSLINK
Power	Barrel Connector
RS-232	3-pin Phoenix connector (mating connector not
	included)
USB	Type-B receptacle (USB 2.0)
USB	
USB 2.0	Microphones and speakers connect to PCs using
035 2.0	standard UAC/UVC drivers
	Standard Orter ove arrivers
	USB connection used to configure AMX Acendo Vibe
	using PC application
PLUSTOOTU 4.0	
BLUETOOTH 4.0	
Supported Profiles	Hands-Free Profile
	Advanced Audio Distribution Profile
AUDIO	
Supported	Stereo 10 W/Channel Amplifier
	Built-in Acoustic Echo Cancellation
DEMOTE CONTROL	
REMOTE CONTROL	
Supports the following	Connects to Vibe using Bluetooth
	Functions:
	Bluetooth Pairing for mobile devices
	Disconnect (Hang Up)
	Microphone Mute
	Source Select
	Volume Up/Down
	Volume Mute

REGULATORY COMPLIANCE	
Regulatory Compliance	FCC 47 CFR Part 15, Subpart C / Subpart B (emissions) UL 60950-1 CE EN 55024 CE EN 60950-1 IEC 60950-1

ENVIRONMENTAL	
Temperature (Operating)	32° F to 122° F (0° C to 50° C)
Temperature (Storage)	-4° F to 158° F (-20° C to 70° C)
Humidity (Operating)	5% to 85% RH non-condensing

ACTIVE POWER REQUIREMENTS	
Voltage, AC (Typical)	12-16 VDC. Note: the maximum amplifier power will be lower at lower input voltages.
Power Consumption (Max)	TBA

About AMX by HARMAN

Founded in 1982 and acquired by HARMAN in 2014, AMX® is dedicated to providing AV solutions for an IT World. AMX solves the complexity of managing technology with reliable, consistent and scalable systems comprising control, video switching and distribution, digital signage and technology management. AMX systems are deployed worldwide in conference rooms, classrooms, network operation/command centers, homes, hotels, entertainment venues and broadcast facilities, among others. AMX is part of the HARMAN Professional Group, the only total audio, video, lighting, and control vendor in the professional AV market. HARMAN designs, manufactures and markets premier audio, video, infotainment and integrated control solutions for the automotive, consumer and professional markets. Revised 6.5.17. ©2017 Harman. All rights reserved. Specifications subject to change. www.amx.com | +1.469.624.7400 | 800.222.0193