

COLS41

slimline column speaker for speech 100V



Advanced technology guarantees optimized sound dispersion and improved speech intelligibility. This decreases microphone feedback in reverberant locations such as houses of worship, sport facilities, public buildings as well as conference facilities and auditoriums.

This speaker offers timeless design combined with impeccable sound reproduction.

The COLS41 has 4 x 2" woofers and 1 x 1" tweeter. A standard wall bracket and installation tools are included.

The COLS41 loudspeakers can be painted in any colour.

TECHNICAL SPECIFICATIONS

height in mm	400	width in mm	66
depth in mm	66	loudspeaker system	multiple
woofer size in inch	4 x 2	woofer cone material	coated paper
tweeter size in inch	1	mounting system	L-brackets
colour	white	100V transformer power taps in	20 - 10 -5
impedance (ohms)	8	watts	
SPL 1W/1m in dB	88	low impedance dynamic power in watts	30
frequency response in Hz	250 - 20K	max SPL 1m in dB	100
grille main material	aluminium	main construction material	aluminium
Horizontal dispersion angle	180°	IP rating	66
1000 Hz		Vertical dispersion angle 1000	110°
Net weight product (kg)	1,75	Hz	110



MORE PICTURES





ACCESSORIES



COLSBRA

Bracket for easy tilting and rotating of COLS sound columns