

# MA240

## Professional mixing amplifier 240W



The revolutionary 19" MA240 mixing amplifier offers 240 watts in 70 or 100 volt mode and comes with 2 mic/line input and 4 stereo line, mono summed inputs. On the rear you can find smart left-to-right 4 level priority system for audio routing, an emergency input, paging mic with chime and a 24VDC override output.

The MA240 has an unseen intuitive user friendly interface and ground breaking logical rear panel. Installing or operating this amplifier is a true pleasure for every installer and end-user worldwide.

### TECHNICAL SPECIFICATIONS

|                                         |                         |                                    |           |
|-----------------------------------------|-------------------------|------------------------------------|-----------|
| 19" (483 mm wide) rack mounting         | yes                     | height- rack units (1U=44 mm) in U | 2         |
| depth (build in) in mm                  | 290                     | depth (incl front) in mm           | 300       |
| power supply                            | 100 - 240 VAC           | power consumption (max) in watts   | 320       |
| output power RMS 100 volts in watts     | 240                     | output power RMS 4 ohms in watts   | 240       |
| dynamic output power 100 volts in watts | 240                     | minimum impedance load in ohms     | 4         |
| output power tapings                    | 70 - 100 volts - 4 ohms | zone outputs                       | 1         |
| MIC inputs balanced                     | 3                       | inputs with Phantom power          | 2         |
| line input unbalanced                   | 4                       | tone control                       | yes       |
| priority switch                         | 2                       | VOX mute                           | yes       |
| chime                                   | yes                     | emergency input                    | 1         |
| priority output                         | 1                       | priority levels                    | 4         |
| power amp topology                      | class-D                 | frequency response (in Hz)         | 60 - 20 k |
| cooling system                          | convection              | applicable in 100V                 | yes       |
| applicable low impedance                | yes                     | Net weight product (kg)            | 6         |

MORE PICTURES

